

# KENWOOD

## TK-2207/3207

Compact VHF/UHF FM Portable Radios

Kenwood's compact TK-2207/3207 transceiver, based on a proven design, represents ergonomic excellence. Pick one up and you'll immediately appreciate how easy it is to use. Powerful too, offering priority scan, built-in VOX, a voice scrambler and numerous other features. Plus you can count on reliable performance in all conditions, thanks to MIL-STD 810 & IP54/55 weather-proofing. Indoors or out, rain or shine, the smart new TK-2207/3207 is a star performer!



### COMPACT DESIGN

The TK-2207/3207's rounded ergonomic contours naturally fit the hand for a comfortable hold, while the non-slip elastomer channel knob with improved torque characteristics ensures positive select operation.

### PRIORITY SCAN & TALK BACK

Scanning is a simple way to monitor multiple channels and the TK-2207/3207 (16-channel capacity) offers both standard and priority scan modes. Talk Back allows immediate response to a received call without having to manually search or change channels.

### VOICE GUIDE

A synthesized Voice Guide feature can automatically "read out" (in English) the selected channel number; it can also be used when scanning. This eyes-free user interface adds a new dimension for portables worn on a belt, in a pocket or in dimly lit environments. Also, you are less likely to miss a call as a result of an accidental channel change.

### INTERNAL VOX/HANDS FREE READY

Enjoy the convenience of hands-free operation using the optional KHS-21 or KHS-1 headset accessory. The internal VOX (voice-operated transmission) provides PTT control with the simple act of talking. VOX is great for specialized tasks and events where hands-free, constant or repetitive communications are necessary (10-level sensitivity adjustment).

### BUILT-IN VOICE SCRAMBLER

A voice-inversion scrambler provides basic communications security against casual eavesdropping. It can also be used to ensure confidential communications with TK-2160/3160 transceivers.

### FleetSync™ PTT ID & SELCALL

The TK-2207/3207 uses Kenwood's FleetSync™ PTT ID protocol to identify units to a FleetSync™-capable dispatch operation. Alternatively, the PTT ID function can be set per channel to encode one of eight Fleet List ID's for selective calling of groups or individual units.

### QT/DQT/DTMF

The industry standard tone/code squelching formats QT and DQT provide system access and group segregation on shared frequencies. DTMF PTT ID is included for dispatch operations or for a simple remote control application. The DTMF decode capabilities include a selective call ID, transpond with ID, "wild card" group calling and radio stun. Both selective calling formats (FleetSync™ and DTMF) have call alert tones and LED indications.

### PROGRAMMABLE FUNCTION KEYS

The two side PF Keys are programmable for any of the many functions available on the TK-2207/3207, permitting a customized fit for specific users.

### OPTIMUM AUDIO

Clear audio means confident communications. The TK-2207/3207 is equipped with a large speaker offering a full half-watt of audio output, while tailored response characteristics provide optimum clarity even in noisy environments.

### 14-HOUR BATTERY PACK

The standard KNB-29N Ni-MH 14-hour\* pack offers extended power in a compact, lightweight design.

\*Battery life is based on a 5% transmit / 5% receive / 90% standby duty cycle.

### TOUGH & WATER RESISTANT

Built tough to take rough treatment in stride, the TK-2207/3207 has passed the advanced IP54/55 and MIL-STD 810 "blowing rain" water resistance tests. It also meets or exceeds 11 other stringent MIL-STD 810 C/D/E/F environmental standards. Whatever the weather, the TK-2207/3207 is ready to answer the call.

### OTHER FEATURES

- Key Lock
- Wireless clone
- Selectable microphone sensitivity (2-level FPU set)



## Options

### ■ KNB-29N

Ni-MH Battery Pack  
(1,500mAh)



### ■ KSC-31

Rapid Charger (3H)



### ■ KRA-22

VHF Low Profile  
Helical Antenna



### ■ KRA-23

UHF Low Profile  
Helical Antenna



### ■ KRA-26

VHF Helical Antenna



### ■ KRA-27

UHF Whip Antenna



### ■ KMC-17

Speaker Microphone



### ■ KMC-21

Compact Speaker  
Microphone



### ■ KHS-1

Head Set with VOX/PTT



### ■ KHS-21

Head Set



### ■ KBH-10

Belt Clip



### ■ KWR-1

Water Resistant Bag



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

## Specifications

	TK-2207	TK-3207
<b>GENERAL</b>		
Frequency Range		
Type 1	136-174 MHz	450-490MHz
Number of Channels	16	
Channel Spacing		
Wide/Narrow	25kHz/12.5kHz	
Channel Step	5, 6.25kHz	
Operating Voltage	7.5V DC±20%	
Battery Life (5-5-90 duty cycle with battery saver off)		
with KNB-29N (1500mAh)	Approx. 14 hours	
Operating Temperature Range	-30°C ~ +60°C	
	-10°C ~ +60°C when KNB-29N in use	
Frequency Stability	±2.5ppm (-30°C ~ +60°C)	
Antenna Impedance	50Ω	
Channel Frequency Spread		
Type 1	38MHz	40MHz
Dimensions (W x H x D), Projections not included		
Radio Only	54 x 122 x 21.1 mm	
with KNB-29N	54 x 122 x 33 mm	
Weight (net)		
Radio Only	160 g	
with KNB-29N	360g	

	TK-2207	TK-3207
<b>RECEIVER</b> (Measurements made per TIA/EIA-603)		
Sensitivity (12dB SINAD)		
Wide/Narrow	0.25µV/0.28µV	
Selectivity		
Wide/Narrow	70dB/60dB	
Intermodulation Distortion		
Wide/Narrow	65dB/60dB	
Spurious Response	65dB	60dB
Audio Output	500mW with less than 10% distortion	
<b>TRANSMITTER</b> (Measurements made per TIA/EIA-603)		
RF Power Output		
High/Low	5W/1W	4W/1W
Spurious Response	65dB	
Modulation		
Wide/Narrow	16K0F3E/11K0F3E	
FM Noise		
Wide/Narrow	45/40dB	
Audio Distortion	Less than 5%	

Kenwood reserves the right to change specifications and features without prior notice. FleetSync™ is a trademark of Kenwood Corporation.

## Applicable MIL-STD

Military Standards	Methods/Procedures MIL-STD 810C	Methods/Procedures MIL-STD 810D	Methods/Procedures MIL-STD 810E	Methods/Procedures MIL-STD 810F
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV

\*Rain (Drip/Blowing Rain): assumes that the supplied accessory jack cover or a Kenwood audio accessory is installed.



# KENWOOD CORPORATION

2967-3, Ishikawa-machi, Hachioji-shi, Tokyo, 192-8525 Japan